

Optical fiber-driven low-energy electron gun for time-resolved streak diffraction

Chiwon Lee¹, Günther H. Kassier¹, and R. J. Dwayne Miller^{1,2,*}

¹Max Planck Institute for the Structure and Dynamics of Matters, Luruper Chaussee 149, 22607, Hamburg, Germany

²Departments of Chemistry and Physics, University of Toronto, M5S 3H6, Ontario, Canada

Abstract. The wave guiding feature of the optical fibre optical fibres is specifically exploited to construct a novel type of electron gun to realize single-shot low-energy electron diffraction experiments with the sub-picosecond resolution for studying irreversible samples.

1 Introduction

In contrast to the conventional stroboscopic pump-probe scheme using hundreds of short bunches, the ultrafast streak diffraction technique exploits, ideally, a single long (typically few picoseconds) electron bunch in which time-varying structure information is encoded after photo-excitation of diffraction samples being probed by electron diffraction [1,2]. The long electron bunch acts as an observable time-window of the dynamics from which different temporal components are separated in space under a transient electric field generated inside the streak camera. Here, we present an optical fiber-based ultrafast low-energy electron gun developed for time-resolved streak electron diffraction. We find a new robust mean to actively control the electron bunch length by exploiting dispersion effects of the optical fiber used for the photocathode substrate, and therefore, opening the possibility to optimize the time-window for time-resolved streak electron diffraction by tailoring geometrical parameters of the fibre and its coupling to the laser beam. Compared to conventional methods (for example, RF field induced bunch broadening or pulse stretching by using grating pairs) to deliver the picosecond long photoinjection pulses stretched from femtosecond laser pulses, our electron gun concept is relatively simple and combines all these features in a fiber optic based device.

2 Experimental

The optical fibre-based photocathode [3] is prepared by direct coating of 30 nm gold on the polished surface of the metallic fibre ferrule in which the multimode fibre is connectorized by using epoxy glue as shown in Fig. 1(a), (b), (c). The core and cladding diameter of the fibre is selected to 100 μm and 125 μm , respectively, for the efficient coupling between the free space UV pulse to the fibre end. The gold-coated fibre ferrule is mounted to a ferrule

* Corresponding author: dwayne.miller@mpsd.mpg.de

bunch composed of 200 electrons, indicating that the space charge effect is negligible for the temporal property of the non-dense electron bunch triggered by the stretched pulse in the range of the FWHM pulse width from 2.4 ps to 14.1 ps. In contrast, for bunches with more than 104 electrons, the bunch length starts to broaden upon propagation even in the case of maximally stretched pulses in the simulation (Fig. 4 (e)). As summarized in Fig. 4 (g), this bunch broadening tendency is significant as the number of electrons per bunch becomes larger and when the pulse width of the trigger is shorter.




Fig. 3. (a) Temporal characteristics of the electron bunch. For the experiment and simulation, the electron energy was set to 1.6 keV. (a) Unstreaked and (b) streaked electron beam image. The scale bar indicates 10 pixels. The intensity profile of these two images are binned horizontally and deconvolved each other with Tikhonov regularization parameter of 2.4 to generate the temporal profile of the electron bunch shown in (c). (d) Calculated FWHM length of the bunch as a function of the trigger pulse width (with 200 electrons), and (e) the number of electrons per bunch (with 14.1 ps trigger pulse) (f) Calculated FWHM length of the bunch measured at the diffraction sample position (5 mm far from the electron gun).

3 Summary

In summary, we have demonstrated an optical fiber-based electron gun integrated with an electrostatic Einzel lens system developed for the purpose of ultrafast streak electron diffraction. Temporal characteristics of the generated electron bunch and simulation results indicate that the temporal length of the non-dense electron bunch triggered by few picosecond laser pulse stretched inside the fiber is minimally affected by space charge effects. The picosecond electron bunch provides the optimal time window to catch entire dynamics of diffraction samples, and can be streaked to decode the information on sub-ps time scale. Therefore, the combination of this relatively long electron pulse duration and steaking technique enables the study of surface-sensitive samples, the ideal target for this low-energy electron probe, with femtosecond resolution in low-energy electron diffraction experiments.

4 References

1. M. Eichberger, N. Erasmus, K. Haupt, G. Kassier, A. von Flotow, J. Demsar, and H. Schwoerer, *Appl. Phys. Lett.* **102**, 121106 (2013)
2. P. Musumeci, J. T. Moody, C. M. Scoby, M. S. Gutierrez, M. Westfall, and R. K. Li, *J. Appl. Phys.* **108**, 114513 (2010).
3. A. Casanandruc, R. Bucker, G. Kassier, and R.J.D. Miller, *Appl. Phys. Lett.* **109**, 091105 (2016)
4. See <http://www.cst.com>
5. G. H. Kassier, K. Haupt, N. Erasmus, E. G. Rohwer, H. M. V. Bergmann, H. Schwoerer, S.M.M. Coelho, and F.D. Auret, *Rev. Sci. Instru.* **81**, 105103 (2010)
6. See <http://www.desy.de/mpyflo/>